




Picture



Features

- CE/CB Approved Emergency Light Model DT series
- Injection-molded plastic ABS housing
- Easy installation and maintenance
- Energy-saving LEDs with long operating lifespan of up to 100,000 hours
- Over-charged and over-discharged battery protections
- Test button to test emergency lighting set in normal operating
- LED indicator to monitor battery operating
- Emergency duration: 1.5 hours
- Maximum 48 hours for full recharge t

Dimension (mm)



Specifications

Items	Units	Parameter
Input Voltage	V	AC110-240V
Source Type	-	SMD LED 36x0.07
Luminous Flux	lm	300
Brightness	cd/m2	>15
Beam Angle	°	140
Body Materials	-	ABS
Life Time	Hr	50000
Work Temperature	°C	0~50
Emergency Time	Hr	1.5
Consumption Power	W	4
Battery	-	Ni-Cd 3.6V 900mAh
Emergency Convension Time	s	< 1
Charge time	Hr	48
Net Weight/pc (with battery)	g	315
One Pieces Packing	mm	139x213x55

Product Name	EMERGENCY LED LIGHTS DT Series
Model No.	DT-130
Main Specification	36x0.07W SMD LED ABS Housing 300lm
Product Size	104.5x50x209
MOQ	500PCS
Lead Time	35 days
Sample Delivery Time	3~10 days
Remarks:	

Packing Information

Packing:	White box				
Carton:	L(cm)		W(cm)		H(cm)
Carton Size:	44.2		32.5		30
Carton CBM:	0.059M3				
Q'TY/INNER BOX:	1PCS				
Q'TY/CTN:	20PCS				
Gross Weight:	7.9KGS				
Net Weight:	8.6KGS				
Container Loading	1*20'		1*40'		1*40' HQ
Q'TY(PCS):					

