




Picture



Dimension (mm)



Features

- CE/CB Approved Emergency Light Model DT series
- Injection-molded plastic ABS housing
- Easy installation and maintenance
- Energy-saving LEDs with long operating lifespan of up to 100,000 hours
- Over-charged and over-discharged battery protections
- Test button to test emergency lighting set in normal operating
- LED indicator to monitor battery operating
- Emergency duration: 3 hours
- Maximum 48 hours for full recharge t

Specifications

Items	Units	Parameter
Input Voltage	V	AC100-240V
Source Type	-	SMD LED 24pcsx0.07
Luminous Flux	lm	100
Brightness	cd/m2	>15
Beam Angle	?	140
Body Materials	-	ABS
Life Time	Hr	50000
Work Temperature	°C	0~50
Emergency Time	Hr	3
Consumption Power	W	4
Battery	-	3.7V1A Lithium battery
Emergency Convension Time	s	< 1
Charge time	Hr	48
Net Weight/pc (with battery)	g	220
One Pieces Packing	mm	177x86x48

Packing Information

Packing:	White box			
Carton:	L(cm)	W(cm)	H(cm)	
Carton Size:	37	28.5	28.2	
Carton CBM:	0.0298M3			
Q'TY/INNER BOX:	1PCS			
Q'TY/CTN:	30PCS			
Gross Weight:	7.8KGS			
Net Weight:	8.6KGS			
Container Loading	1*20'	1*40'	1*40' HQ	
Q'TY(PCS):				

Product Name	EMERGENCY LED LIGHTS DT Series
Model No.	DT-168
Main Specification	24x0.07W SMD LED ABS Housing 200lm
Product Size	170x80x45
MOQ	500PCS
Lead Time	35 days
Sample Delivery Time	3~10 days
Remarks:	

